

MANNINGTON COMMERCIAL

INFINITY® RE

CONSTRUCTION SPECIFICATIONS

PRIMARY SUBSTRATE:	100% Synthetic
PRECOAT LAYER:	100% Vinyl Non-Aqueous Polymer
STABILIZING LAYER:	Non-woven Fiberglass
SECONDARY LAYER:	Vinyl Composite Non-Aqueous Recycled Pre-Consumer Carpet and Resilient
RECYCLED CONTENT:	Pre-Consumer Carpet and Resilient and 10% minimum Post-consumer recycled content by total weight of product
TOTAL BACKING WEIGHT:	Approx. 110 ounces per square yard
THICKNESS:	.100 inches (approximate)
MODULAR SIZE:	24" X 24"

PERFORMANCE SPECIFICATIONS

METHENAMINE PILL TEST: (FF 1-70)	PASSES
RADIANT PANEL TEST: (ASTM E-648)	CLASS I
NBS SMOKE TEST: (ASTM E-662)	450 OR LESS (FLAMING MODE)
INDOOR AIR QUALITY:	PASSES CRI GREEN LABEL PLUS
DIMENSIONAL STABILITY: (AACHEN TEST)	PASSES
WARRANTY:	LIMITED LIFETIME WARRANTY